Express Mail No.: <u>EV459189775US</u> 9D-DW-19893 PATENT

IN THE CLAIMS:

1. (currently amended) An escutcheon for an appliance door assembly, said

escutcheon comprising:

a front edge and a rear edge horizontally spaced from said front edge, said front and

rear edges vertically depending from an escutcheon upper surface;

a control panel mounting surface comprising a lower edge, said control panel

mounting surface extending upwardly and inwardly from said lower edge and between said

front and rear edges, said control panel mounting surface including a plurality of openings

therethrough; and

a plurality of formations downwardly depending from said lower edge and defining a

retaining slot, said retaining slot configured to receive an upper edge of a panel on the

appliance door.

2. (original) An escutcheon in accordance with Claim 1 wherein said formations

comprise panel positioning ribs.

3. (withdrawn) An escutcheon in accordance with Claim 2 wherein the door

assembly includes an outer panel with a curved outer surface, said ribs arranged beneath said

lower edge to approximately match the curvature of the outer panel.

4. (previously presented) An escutcheon in accordance with Claim 2 wherein said

ribs comprise a guide surface extending at an acute angle with said lower edge.

5. (original) An escutcheon in accordance with Claim 4, said ribs further comprising

a panel engagement portion extending from said guide surface.

6. (withdrawn) An escutcheon in accordance with Claim 1 further comprising a

curved front face extending beneath said lower edge.

2

Express Mail No.: <u>EV459189775US</u> 9D-DW-19893 PATENT

7. (currently amended) An escutcheon for a dishwasher door assembly, said escutcheon comprising a lower edge and a plurality of formations depending therefrom, each formation comprising a guide surface formed at an acute angle with said lower edge, said guide surface defining a retaining slot, said guide surface defining a panel engagement portion, and said retaining slot configured to receive an upper edge of a panel on the dishwasher door.

- 8. (original) An escutcheon in accordance with Claim 7 further comprising a lip, said slot defined by said guide surface and said lip.
- 9. (previously presented) An escutcheon in accordance with Claim 8 wherein_said panel engagement portion extends_substantially parallel to said lip.
- 10. (withdrawn) An escutcheon in accordance with Claim 7 wherein said formations are located along a curved path.
- 11. (withdrawn) An escutcheon in accordance with Claim 10 further comprising a control panel mounting surface, and a curved front face extending between said control panel mounting surface.
 - 12. (withdrawn) An appliance door assembly comprising:

an outer door panel comprising an edge and an outer surface; and

an escutcheon attached to said edge, said escutcheon comprising a plurality of formations defining a retaining slot, said formations locating said outer surface within said slot when said edge is received in said slot.

13. (withdrawn) A door assembly in accordance with Claim 12, said formations comprising a panel engagement portion and a guide surface extending at an angle from said panel engagement portion.

Express Mail No.: <u>EV459189775US</u> 9D-DW-19893 PATENT

14. (withdrawn) A door assembly in accordance with Claim 13 wherein said panel outer surface is curved, said formations depending from said escutcheon in a curved arrangement.

- 15. (withdrawn) A door assembly in accordance with Claim 12, said escutcheon comprising a lip defining said retaining slot, said panel engagement portion extending substantially parallel to said lip.
- 16. (withdrawn) A door assembly in accordance with Claim 12, said escutcheon comprising a lower edge, said lower edge substantially flush with said panel outer surface when said edge is received in said slot.
- 17. (withdrawn) A door assembly in accordance with Claim 16 wherein said panel outer surface is curved.
 - 18. (withdrawn) A dishwasher door assembly comprising:

an outer door panel comprising an edge and a curved outer surface; and

an escutcheon attached to said edge, said escutcheon comprising a plurality of formations defining a retaining slot, each said formation comprising a panel engagement portion, said panel engagement portion positioning said edge within said slot to that said panel outer surface is substantially flush with an outer surface of said escutcheon.

- 19. (withdrawn) A door assembly in accordance with Claim 18, each said formation further comprising an angled guide surface extending from said panel engagement portion.
- 20. (withdrawn) A door assembly in accordance with Claim 18 wherein said outer surface of said escutcheon is curved.